

**Declaration of Performance  
No. 002/DoP/01/09/2022 REVISION N° 3**

In accordance with Regulation ( EU ) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products ( CPR EU 305/2011 )

1. Unique identification code of product-type:

**Fibre-cement profiled sheets and fittings NT**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 ( 4 ).

**Provenzali Secursil / Secursil R and fittings**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Profiled sheets and fittings for roofing ( roof coverings ) or cladding  
( internal and external wall finishes )**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 ( 5 ) :

**Società Italiana Lastre SpA**  
**Via Lenzi, 26 Verolanuova, Brescia, Italy**  
**Tel 0039-030-9920900 Fax 0039-030-9920884**  
**e-mail: [info@sil-lastre.com](mailto:info@sil-lastre.com)**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 ( 2 ):

**n.a**

6. System or system of assessment and verification of constancy of performance of the construction product as out in Annex V:

**System 3**

7. Name and identification number of the notified body ( in case of the declaration of performance concerning a construction product covered by a harmonised standard ) :

**CSI SpA**  
**Viale Lombardia, 20**  
**20021 Bollate MI – Italy**  
**Notified body No. 0497**

Within the scope of the harmonized standard EN 494:2012+A1:2015 CSI SpA (NoBo no. 0497) determined this Product Type on the basis of Initial Type Testing and issued the certificate of Type Examination No.

**CSI-CERT-No. DE/2098**



8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Mechanical resistance	C1X	EN 494:2012+A1:2015 Fibre-cement profiled sheets and fittings Product specification and test methods
Breaking load	Min 4250N/m	
Bending moment	Min 55Nm/m	
Apparent density	≥ 1,35 g/cm <sup>3</sup>	
Impact resistance	Pass	
External fire performance	B <sub>ROOF</sub> ( deemed to satisfy )	
Reaction to fire*	Class A1	
Water impermeability	Pass	
Dimensional variations		
Length*	± 10 mm	
Width*	+10/ -5 mm	
Thickness*	6,5 ± 0,5 mm	
Height of the corrugations*	60 ± 3 mm	
Pitch*	230 ± 2 mm	
Squareness	max 6 mm/m	
Release of dangerous substances*	No performance determined ( NPD )	
Durability against warm water	R <sub>L</sub> ≥ 0,70	
Durability against soak/dry	R <sub>L</sub> ≥ 0,70	
Durability against freeze-thaw	R <sub>L</sub> ≥ 0,70	
Durability against heat - rain	Pass	

\* Performance applied to accessories. All performances apply to corrugated sheets.

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ing Gianenrico Bonetti

Legal representative of Società Italiana Lastre SpA

Verolanuova, 01/09/2022

Signature.....